



- Notes:
- Materials and treatment:
 - Outer shell : Stainless steel, passivated.
 - Contact : Beryllium copper, gold plating.
 - Insulator : PTFE
 - Cover : Stainless steel, passivated.
 - Specifications:
 - Electrical performance:
 - Impedance : 50Ω
 - Frequency : 40GHz
 - Insertion loss : 0.3dB
 - Return loss : 34dB
 - Shielding effectiveness : 100dB
 - Contact resistance : 0.75mΩ
 - RoHS Directive Compliance.(2015/863/EU)

ENGINEERING CORPORATION
 ISSUE DATE
 2021/12/21
nexttron
 This file is automatically issued by EPDM and is not valid without the issue date

00	NEW RELEASE	2021/12/16
REV.	DESCRIPTION	DATE

UNITS: ■ mm □ inch	SIZE A3	NAME: Coaxial Connector- 2.92mm Female Flange	 NEXTRONICS ENGINEERING CORP.								
GENERAL TOLERANCE: (UNLESS SPECIFIED)		PART NO: 000013	TITLE: CUSTOMER DWG.								
	mm	inch	APPD: Alan蘇侯安	2021/12/18	DWG NO: 010-000013						
4 PLACE	± **	±. **	CHKD: Alan蘇侯安	2021/12/18							
3 PLACE	± **	±. **	DRAW: Sunny鄭竹晴	2021/12/17	<table border="1"> <tr> <td>SCALE</td> <td>SHEET</td> <td>REV.</td> </tr> <tr> <td>7/1</td> <td>1/1</td> <td>00</td> </tr> </table>	SCALE	SHEET	REV.	7/1	1/1	00
SCALE	SHEET	REV.									
7/1	1/1	00									
2 PLACE	± 0.20	±. **	DESIGN: Ellen孫郁婷	2021/12/17							
1 PLACE	± 0.30	±. **									
ANGLES	X° ± 2										

CONFIDENTIAL: THIS DOCUMENT CONTAINED THE INFORMATION IS PROPRIETARY AND CONFIDENTIAL TO Nextronics Engineering Corp. NO PERSON IS ALLOWED TO USE COPY, PUBLISH OR OTHERWISE DISCLOSE THE INFORMATION TO OTHERS, UNLESS BY THE PRIOR WRITTEN EXPRESS AUTHORIZATION OF Nextronics Engineering Corp. (C)COPYRIGHT- Nextronics Engineering Corp.